

DYNAMITE POOL PATCH

Description:

Pool patch is a mixture of portland cement and special additives that permits underwater patching and general concrete repair work to be done instantly. Pool patch can be used wherever a quick setting caulking or plugging material is needed.

Uses:

Underwater pool repair
Underwater concrete repair
New construction
Remodeling

Characteristics:

High Strength
Sets underwater
Brilliant white

Preparation:

Repair area must be clean and free of any paint, dust or grease, Chisel V-shaped channel to allow easy application wherever possible. Dampen area prior to application.

Application:

Mix approximately one (1) part water to three (3) parts pool patch or until material has a dough like consistency. Warning: Warm water will accelerate set time of patch. Mix only as much as can be used in 3-5 minutes. Using a steel trowel or pointed tool, force material into hole or crack. To repair water leaks or for under-water use, apply pressure for a minimum of five (5) minutes or until material has firmly set. Dampen material for fifteen (15) minutes after patching to prevent cracking.

Curing:

Minimum cure is reached in fifteen (15) minutes. Dampen material to prevent cracking during first initial fifteen (15) minutes.

Caution:

Warning - Eye Irritant Contains Portland Cement.
Product is alkaline on contact with water. Use paddle for mixing to avoid splashing into eyes or contact with skin. During mixing or application, avoid contact with eyes. In case of such contact, flood eyes repeatedly with water and CALL PHYSICIAN. Wash thoroughly after handling and before smoking or eating. Do not take internally. Keep out of reach of children.=

Shelf Life:

Up to nine months from date of mfg. in unopened container.

Packaging:

3 lbs.35/kg)
9 lbs. (4.09/kg)
60 lbs. (27.24/kg)

SGM

Pompano Beach, FL – Dallas, TX – Corona, CA – Plant City, FL

Phone: 800.641.9247

1502 SW 2nd Place, Pompano Beach, FL 33069

FAX: 954.943-2402

www.sgm.cc