



INSTANT HYDRAULIC CEMENT

Instant Hydraulic Cement is a mixture of specialty cement and proprietary additives that permits underwater patching and general concrete repair work to be done instantly. Instant Cement can be used wherever a quick setting caulking or plugging material is needed.

MANUFACTURER:

SGM, Inc.
1502 SW 2nd Place
Pompano Beach, FL 33069-3220
(800) 641-9247
(954) 943-2288
Fax: (954) 943-2402
www.sgm.cc
sales@sgm.cc

TECHNICAL DATA:

To date, no specifications have been industry approved. Our material is tested and certified by independent laboratories. All data is given in good faith, however, we reserve the right to change products and specifications without notice. SGM advises interested parties to satisfy themselves as to the accuracy of any data and seek certification if appropriate.

USES:

- Seawalls
- Foundations
- Sewer pipes
- Pools
- Basements
- Manholes

PACKAGING:

5 Gallons (27.24kg)

SHELF LIFE:

Up to six months from date of manufacturing in unopened container.

SURFACE PREPARATION:

Repair area must be clean and free of any paint, dust or grease. Chisel V-shaped channel to allow

easy application wherever possible. Dampen area to be repaired.

MIXING:

Mix approximately 3 parts Instant Cement to 1 part water or until material becomes a dough-like consistency. WARNING - Warm water will accelerate set time. Only mix as much material that can be used in 3-5 minutes.

APPLICATION:

With pointing tool or steel trowel force material into hole or crack. Dampen material for 15 minutes after patching to prevent cracking. To repair water leak or underwater, apply pressure to material for a minimum of 5 minutes or until materials has firmly set.

WARNING:

Product is Alkaline on contact with water. Use paddle for mixing to avoid splashing into eyes or contact with skin. During mixing or application, avoid contact with eyes. In case of such contact, flood eyes repeatedly with water and CALL PHYSICIAN. Wash thoroughly after handling and before smoking or eating. Do not take internally. WARNING: This product can expose you to chemicals including silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov. Wear NIOSH approved mask for Silica dust. KEEP OUT OF REACH OF CHILDREN.

WARRANTY:

SGM Inc. warrants this product will perform in accordance with its intended use for a period of one year from the date of manufacture. Any claim for defective product must be submitted in writing to SGM Inc. and samples

of defect must be provided. IN NO EVENT SHALL SGM INC. BE LIABLE FOR DAMAGES OF ANY KIND OR NATURE, WHETHER ARISING BY CONTRACT, TORT OR OTHERWISE. SGM INC.'S SOLE OBLIGATION WILL BE TO REPLACE ANY PRODUCT DETERMINED BY SGM INC. TO BE DEFECTIVE. Your acceptance or use of this product is your agreement that Broward County, Florida, and Florida law is the exclusive jurisdiction and venue for all purposes.

TECHNICAL SERVICES:

Technical assistance, including more detailed information, product literature, test results, project list, samples, assistance in preparing project specifications and arrangements for job site inspection and supervision, is available by contacting Technical Services Department.

(800) 641-9247
(954) 943-2288
Fax: (954) 943-2402
www.sgm.cc
ts@sgm.cc



WARNING: This product can expose you to chemicals including silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

10/20/22