



SAND TOPPING

Ready to use sand/cement topping mix.

MANUFACTURER:

SGM, Inc.
1502 SW 2nd Place
Pompano Beach, FL 33069-3220
(800) 641-9247
(954) 943-2288
Fax: (954) 943-2402
www.sgm.cc
sales@sgm.cc

TECHNICAL DATA:

APPLICABLE STANDARDS

ASTM International (ASTM)
COMPLIES WITH ASTM C387
Standard Specification for Packaged,
Dry Combined Materials for Mortar and
Concrete.

SGM Sand Topping mix exceeds the
compressive strength requirements for
high strength mortars per ASTM C387
Typical compressive strengths:
Greater than 2,500 psi at 28 days.

Our material is tested and certified
by independent laboratories. All data
is given in good faith, however, we
reserve the right to change products
and specifications without notice.
SGM advises interested parties to
satisfy themselves as to the accuracy
of any data and seek certification if
appropriate.

USES:

- For patching concrete, filling cracks
and topping concrete.
- Applications 1/2" to 2" (12.7mm-
50mm)
- Ideal for use as a mortar
bed under ceramic tile and
dimension stone applications.

APPLICATION:

Surfaces must be clean of foreign
matter, grease paint and oil. Use
Concrete Bonding Agent prior to

application of Sand Topping over
existing concrete or masonry surfaces
to insure a good mechanical bond.

NOTE: Do not cover expansion,
cold or control joints. Follow TCNA
Handbook method EJ 171 for detailed
specifications.

MIXING:

Mix approximately 6-9 pt. (2.8- 4.3 L) with
clean potable water to desired plastic
like consistency via mechanical barrel
type or mortar mixer.

COVERAGE:

Approximately, and 14 sq. ft. at 1/2"
thickness per 60 lb. bag.

CURING:

Cure time varies according to
atmospheric and job-site conditions.

CLEAN UP:

Use warm soapy water.

SHELF LIFE:

Use within 12 months of the
manufacturing date.

WARNING:

Product is Alkaline on contact with
water. Use paddle for mixing to avoid
splashing into eyes or contact with
skin. During mixing or application,
avoid contact with eyes. In case of
such contact flood eyes repeatedly
with water and CALL PHYSICIAN. Wash
thoroughly after handling and before
smoking or eating. Do not take internally.
CONTAINS FREE SILICA DO NOT
BREATHE DUST. Prolonged exposure to
dust may cause delayed lung disease
(silicosis). WARNING: This product
can expose you to chemicals including
silica, which is known to the State of
California to cause cancer. For more
information go to www.P65Warnings.ca.gov. Wear NIOSH approved mask
for Silica dust. KEEP OUT OF REACH
OF CHILDREN.

WARRANTY:

SGM Inc. warrants this product will
perform in accordance with its intended
use for a period of one year from the
date of manufacture. Any claim for
defective product must be submitted
in writing to SGM Inc. and samples of
defect must be provided. SGM Inc.
sole obligation will be to replace any
product determined to be defective
by SGM Inc. EXCEPT AS PROVIDED
HEREIN, SGM INC. MAKES NO OTHER
REPRESENTATION OR WARRANTY OF
ANY KIND, INCLUDING ANY WARRANTY
OF MERCHANTABILITY OR FITNESS
FOR PARTICULAR PURPOSE. IN NO
EVENT SHALL SGM INC. BE LIABLE FOR
DAMAGES OF ANY KIND OR NATURE,
WHETHER ARISING BY CONTRACT,
TORT OR OTHERWISE. SGM INC.'S
SOLE OBLIGATION WILL BE TO
REPLACE ANY PRODUCT DETERMINED
BY SGM INC. TO BE DEFECTIVE.

TECHNICAL SERVICES:

Technical assistance, including more
detailed information, product literature,
test results, project list, samples,
assistance in preparing project
specifications and arrangements for
job site inspection and supervision, is
available by contacting SGM Technical
Services Department.

(800) 641-9247
(954) 943-2288
Fax: (954) 943-2402
www.sgm.cc
ts@sgm.cc



WARNING: This product can
expose you to chemicals
including silica, which is known
to the State of California to
cause cancer. For more information go
to www.P65Warnings.ca.gov.