

SAFETY DATA SHEET

1. Identification

Product identifier Southcrete 555 Type 1 Adhesive

Other means of identification None

Recommended use Ceramic Tile Adhesive

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier

Company name Southern Grouts and Mortars, Inc.

Address 1502 SW 2nd Place

Pompano Beach, Florida 33069

(954) 943-2288 Telephone number (954) 943-2402 Fax **Contact name Technical Manager** WWW.SGM.CC Website **Emergency telephone** (954) 943-2288

number

Transportation emergency

2. Hazard(s) identification

Label elements



Physical Hazards CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR

> 1910.1200 (OSHA HAZCOM2012) Carcinogenicity - Category 1A STOT-RE - Category 2

Environmental Hazards Not Classified

Signal Words Danger

Hazard Statements May cause cancer

Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

[Response]

[Prevention] Wash hands thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Do not

eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: call a poison center/doctor. If

exposed or concerned: get medical advice/attention.

[STORAGE] Store locked up. Store in a well-ventilated place. Keep container tightly closed.

SDS US Type 1 Adhesive

[DISPOSAL] Dispose of contents/containers in accordance with all local, state, provincial, and federal

regulations.

ADDITIONAL INFORMATION HNOC – HAZARDS NOT OTHERWISE

CLASSIFIED Not applicable

UNKNOWN ACUTE

TOXICITY 4.5% of the mixture consists of ingredient(s) of unknown acute toxicity.

3. Composition/information on ingredients

Chemical Name	CAS Number	Weight %
Calcium Carbonate	1317-65-3	30 – 60%*
Ethylene	107-21-1	1 – 5%*
Petroleum Distillates	64742-88-7 / 64742-47-8	0.1 – 1%*
Crystalline Silica, Quartz	14808-60-7	0.1 – 1%*

^{*}Means that the component will fall into one the ranges specified due to batch-to-batch variability.

4. First-aid measures

ROUTES OF EXPOSURE DESCRIPTION

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses, if worn. Get medical attention immediately.

Skin Contact: In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Get medical advice/attention.

MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE DESCRIPTION

Eye Contact: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear

production, with marked redness and swelling of the conjunctiva.

Skin Contact: May cause skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis.

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or

repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious

disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea

or vomiting.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Not applicable

5. Fire-fighting measures

Flammability:

Suitable Extinguishing

Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding

Not Flammable by WHMIS/OSHA HAZCOM2012 Criteria

environment

Type 1 Adhesive SDS US

Unsuitable Extinguishing

Media: CAUTION: Use of water spray when fighting fire may be inefficient

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon

Explosion Data

Sensitivity to

Mechanical Impact: Not available.

Sensitivity to

Static Discharge: Not available.

6. Accidental release measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT,

AND EMERGENCY PROCEDURES: Use personal protection recommended in Section 8. Isolate the hazard area and deny

entry to unnecessary and unprotected personnel.

METHODS AND MATERIALS FOR **CONTAINMENT AND CLEANING UP**

> **Methods for Containment:** Prevent further leakage or spillage if safe to do so. Do not flush to sewer or allow

> > to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Pick up and transfer to properly labeled containers.

7. Handling and storage

Handling: Use in well-ventilated areas. Wear chemical resistant gloves and eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do

not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Do not take

internally.

General Hygiene Advice: Use good industrial hygiene practices and wear recommended personal protection.

Launder contaminated clothing before reuse. Wash hands before eating, drinking,

or smoking.

CONDITIONS FOR SAFE STORAGE. INCLUDING ANY INCOMPATIBILITIES

Storage: Keep out of the reach of children. Keep container tightly closed.

Store locked up. Store at room temperature and keep containers closed when not in

use.

8. Exposure controls/personal protection

Occupational Exposure Limits

Chemical Name	OSHA-PEL	ACGIH-TLV
Calcium Carbonate	5 mg/m³ (Resp.) 15 mg/m³ (Total)	5 mg/m³ (Resp.)
Ethylene Glycol	50 ppm	50 ppm
Petroleum Distillates	200 mg/m ³	200 mg/m ³
Crystalline Silica, Quartz	0.1 mg/m ³	0.025 mg/m ³

EXPOSURE CONTROLS

Use ventilation adequate to keep exposures (airborne levels of dust, **Engineering Controls:**

fumes, vapor, etc.) below recommended exposure limits.

SDS US Type 1 Adhesive

INDIVIDUAL PROTECTION MEASURES

Personal Protective Equipment:

- i. **Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]
- ii. Skin Protection:
 - 1. Hand Protection: Wear chemical resistant gloves.
 - 2. Body Protection: Wear suitable protective clothing
- **iii. Respiratory Protection:** A NIOSH approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. General Health and Safety Measures: Handle according to established industrial hygiene and safety practices.

9. Physical and chemical properties

Appearance (physical state, color, etc.):	White Paste
Odor:	Latex
Odor Threshold:	Not available
pH:	8.50 – 9.30
Melting point/Freezing point:	Not available
Initial boiling point and boiling range:	Not available
Flash point:	Not available
Evaporation rate (Water=1):	Not available
Flammability:	Not flammable
Upper Flammability/Explosive Limit:	Not available
Lower Flammability/Explosive Limit:	Not available
Vapor Pressure	Not available
Vapor Density:	Not available
Relative Density:	1.20 – 1.35 g/mL
Solubility in Water:	Slightly Soluble
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition Temperature:	Not available
Viscosity (cps):	Not available
VOC Content:	65 g/L

10. Stability and reactivity

REACTIVITY
CHEMICAL STABILITY
POSSIBILITY OF HAZARDOUS REACTION
CONDITIONS TO AVOID
INCOMPATIBLE MATERIALS
HAZARDOUS DECOMPOSITION PRODUCTS

No dangerous reaction known under conditions of normal use. Stable under recommended storage conditions
No dangerous reaction known under conditions of normal use.
Heat. Incompatible materials.
Strong acids and oxidizing agents.
Upon decomposition, this product may yield oxides of carbon

Type 1 Adhesive SDS US

933570 Version #: 01 Revision date: - Issue date: 23-May-2016

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

SYMPTOMS RELATED TO PHYSICAL/ CHEMICAL/TOXICOLOGICAL CHARACTERISTICS

Eye Contact: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking

and tear production, with marked redness and swelling of the conjunctiva.

Skin Contact: May cause skin irritation. Handling can cause dry skin, discomfort, irritation, and

dermatitis.

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged

or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause

silicosis, a serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress,

nausea or vomiting.

Acute Toxicity Total ATE mix (oral) = 8073 mg/kg			
Chemical Name LC50 LD50			
Calcium Carbonate	Not available	Oral: > 5,000 mg/kg, rat	
Ethylene Glycol Inhalation: >2.5 mg/L, rat Oral: 4,700 mg/kg,		Oral: 4,700 mg/kg, rat	
Petroleum Distillates	Petroleum Distillates Inhalation: > 5000ppm, rat Oral: > 5,000 mg/kg, rat		
Crystalline Silica, Quartz	Not available	Not available	

Carcinogenicity		
Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65)	
Calcium Carbonate	Not Listed	
Ethylene Glycol	G-A4	
Petroleum Distillates	Not Listed	
Crystalline Silica, Quartz	N-A2, I-1, O-1, ACGIH-A2, CP65	

DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM			
Skin Corrosion/Irritation:	May cause skin irritation		
Serious Eye Damage/Irritation:	May cause eye irritation		
Respiratory Sensitization:	Not available		
Skin Sensitization:	Not available		
STOT-Single Exposure:	Not available		
Aspiration Hazard:	Not available		
LONG-TERM			
Carcinogenicity:	May cause cancer		
Germ Cell Mutagenicity:	Not available		
Reproductive Toxicity:	Not available		
STOT-Repeated Exposure:	Causes damage to organs through prolonged or		
OTOT Repeated Exposure.	repeated exposure		
Synergistic/Antagonistic Effects:	Not available		

Type 1 Adhesive SDS US

933570 Version #: 01 Revision date: - Issue date: 23-May-2016

12. Ecological information ECOTOXICITY:

iviay cause long-term

May cause long-term, adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity		
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours
Calcium Carbonate	Not available	Not available
Ethylene Glycol	Not available	Not available
Petroleum Distillates	Not available	Not available
Crystalline Silica, Quartz	Not available	Not available

PERSISTENCE AND

DEGRADABILITY: Not available

BIOACCUMULATIVE

POTENTIAL: Not available MOBILITY IN SOIL: Not available

OTHER ADVERSE

EFFECTS: Not available

13. Disposal considerations

DISPOSAL METHOD: Dispose of contents/containers in accordance with all local, state, provincial, and federal

regulations

OTHER DISPOSAL

CONSIDERATIONS: Not available

14. Transport information

DOT (U.S.)	TDG (CANADA)		
UN NUMBER:	UN NUMBER:		
Not regulated	Not regulated		
UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:		
Not regulated	Not regulated		
TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):		
Not regulated	Not regulated		
PACKING GROUP (if applicable):	PACKING GROUP (if applicable):		
Not regulated	Not regulated		

SUMMARY: Product is not regulated under DOT/TDG and other transportation regulations.

ENVIRONMENTAL HAZARDS: Not available

TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78

AND THE IBC CODE: Not available

SPECIAL PRECAUTIONS

FOR USER: Do not handle until all safety precautions have been read and understood.

Type 1 Adhesive SDS US

15. Regulatory information SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

US: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

US FEDERAL INFORMATION:

	SARA TITLE III			
CHEMICAL NAME	SECTION 302	SECTION 304	CERCLA RQ	SECTION 313
	(EHS) TPQ (LBS)	EHS RQ (LBS)	(LBS)	(TRI)
Calcium Carbonate	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene Glycol	Not Listed	Not Listed	5,000	313
Petroleum Distillates	Not Listed	Not Listed	Not Listed	Not Listed
Crystalline Silica, Quartz	Not Listed	Not Listed	Not Listed	Not Listed

US STATE RIGHT TO KNOW LAWS:

California Proposition 65:	WARNING! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm	
Other U.S. States "Right to Know" Lists:	тергоцистие папп	
New Jersey:	Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8	
	Silica, Quartz: CAS#14808-60-7	
Pennsylvania:	Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8 Silica, Quartz: CAS#14808-60-7	
Massachusetts:	Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8 Silica, Quartz: CAS#14808-60-7	
Minnesota:	Calcium Carbonate: CAS#1317-65-3 Ethylene Glycol: CAS#107-21-1 Petroleum Distillate: CAS#64742-88-7 Petroleum Distillate: CAS#64742-47-8 Silica, Quartz: CAS#14808-60-7	
Florida:	Not Available	
Michigan:	Not Available	

SDS US Type 1 Adhesive

GLOBAL INVENTORIES

Chemical Name	USA TSCA	Canada DSL/NDSL
Calcium Carbonate	Yes	NDSL(*)
Ethylene Glycol	Yes	DSL
Petroleum Distillates	Yes	DSL
Crystalline Silica, Quartz	Yes	DSL

Type 1 Adhesive SDS US 933570 Version #: 01 Revision date: - Issue date: 23-May-2016 8 / 9

16. Other information, including date of preparation or last revision

Additional information

Because the product is a mixture, the majority of the data used was transferred from the safety data sheets of the product's hazardous ingredients, whose manufacturer identity we wish to remain anonymous for competitive reasons.

Section 8 Exposure Limits attained from www.osha.gov , www.aiha.org and www.dowcorning.com .

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by the CPR. This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

Type 1 Adhesive SDS US