

SAFETY DATA SHEET

1. Identification

Product identifier Security Polymer Grout

Other means of identificationNone.Recommended useTile grout.Recommended restrictionsNone known.

Manufacturer/Importer/Supplier/Distributor information Supplier

Company name Southern Grouts and Mortars, Inc.

Address 1502 SW 2nd Place

Pompano Beach, Florida 33069

Telephone number (954) 943-2288
Fax (954) 943-2402
Contact name Technical Manager
Website WWW.SGM.CC
Emergency telephone number (954) 943-2288

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated exposure Category 2 (Lung)

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May cause respiratory irritation. May cause damage to organs (Lung) through

prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after

handling. Contaminated work clothing must not be allowed out of the workplace.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Security Polymer Grout SDS US

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Product becomes alkaline when exposed to moisture.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Quartz	14808-60-7	25-80	
Portland Cement	65997-15-1	15-60	
Iron oxide	1309-37-1	0.01-6	
Limestone	1317-65-3	0.01-6	
Other components below reportable levels		7.32	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent

by volume.

4. First-aid measures

Inhalation

Inhalation of wet product not foreseeable route of exposure. If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a POISON CENTER or doctor/physician if

you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Never give anything by mouth to a victim who is unconscious or is having convulsions. DO NOT INDUCE VOMITING. Rinse mouth thoroughly with water and give large amounts of water, if person is

conscious. Get medical attention.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin skin allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed **General information**

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Use fire-extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media None known.

Specific hazards arising from

During fire, hazardous combustion products are released that may include: Carbon oxides (COx).

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

the chemical

equipment/instructions Specific methods

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Security Polymer Grout SDS US

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Prevent entry into waterways, sewer, basements or confined areas. For a dry material spill, use a HEPA (high efficiency particle air) vacuum to collect material and place in a sealable container for disposal. Avoid dust formation. For a wet spill, absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for disposal. Neutralize the spill area. Use materials that can withstand the potentially corrosive nature of this product. Do not get water inside containers. Use materials that can withstand the potentially corrosive nature of this product. Do not get water inside containers. Following product recovery, flush area with water.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

7. Handling and storage Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Static electricity and formation of sparks must be prevented. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage,

Store locked up. Store in original tightly closed container. Store in a well-ventilated place. Store away including any incompatibilities from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Iron oxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Portland Cement (CAS	PEL	5 mg/m3	Respirable fraction.
65997-15-1)			
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 1910.	1000)		
Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	TWA	50 mppcf	
Quartz (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values	;		
Components	Туре	Value	Form
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Portland Cement (CAS	TWA	1 mg/m3	Respirable fraction.
65997-15-1)			
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	Form
Iron oxide (CAS 1309-37-1)	TWA	5 mg/m3	Dust and fume.
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
	TWA	0.05 mg/m3	iolai

Security Polymer Grout

933653 Version #: 01 Revision date: -Issue date: 23-May-2016 **Biological limit values Exposure guidelines**

No biological exposure limits noted for the ingredient(s).

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection

In situations where there is potential splash or puff exposure of cement products, wear safety glasses with side shields or goggles. In extremely dusty or unpredictable environments wear unvented or indirectly vented goggles. Contact lenses should not be worn when working with cement or cement products.

Skin protection

Hand protection Wear protective gloves.

Skin protection

Other

Prevention is essential to avoiding potentially severe skin injury. Avoid contact with unhardened wet Portland cement products. If contact occurs, promptly wash affected area with soap and water. Where prolonged exposure to unhardened Portland cement products might occur, wear impervious clothing and gloves to prevent skin contact. Wear sturdy boots that are impervious to water and eliminate foot and ankle exposure. Do not rely on barrier crèmes; barrier crèmes should not be used in place of gloves.

Respiratory protection

Avoid tasks which cause dust to become airborne. Use local or general ventilation to control exposure below applicable exposure limits. Use NIOSH/MSHA approved (30 CFR 11) or NIOSH approved (42 CFR 84) respirators in poorly ventilated areas, or if an applicable exposure limit is exceeded, or when dust causes discomfort or irritation.

Not available. Thermal hazards

General hygiene considerations

Periodically wash affected areas contacted by dry or wet cement products with a pH neutral soap. When using, do not eat, drink, or smoke. Wash again at the end of work. If clothing becomes saturated with wet cement products, it should be removed and replace with clean dry clothing.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Powder, Coarse Textured Powder.

Color Gray/white. Odorless. Odor Not available. Odor threshold Not available. pН

Initial boiling point and boiling range

Melting point/freezing point

Not available.

Not available. Flash point Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

Not available.

Flammability limit - upper

Not available.

(%)

Not available. **Explosive limit - lower (%)** Explosive limit - upper (%) Not available. Vapor pressure Not available. Not available. Vapor density

Relative density 2.5

Security Polymer Grout SDS US Solubility(ies)

Solubility (water) Miscible. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Explosive properties Not explosive. **Oxidizing properties** Not oxidizing.

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

No dangerous reaction known under conditions of normal use.

reactions

Conditions to avoid Contact with incompatible materials. Moisture. Incompatible materials Powerful oxidizers. Chlorine. Mineral acid.

Hazardous decomposition

products

No hazardous decomposition products are known.

1. Toxicological information

Information on likely routes of exposure

Dust may irritate respiratory system. Contact with moist mucous membranes of the respiratory Inhalation

system can cause a caustic condition resulting in burns. May cause damage to organs through

prolonged or repeated exposure by inhalation.

Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet Skin contact

cement/mixture may cause burns.

Eye contact Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

Ingestion Irritating. May cause nausea, stomach pain and vomiting. Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity May cause respiratory irritation. May cause an allergic skin reaction.

Components **Species Test Results**

Iron oxide (CAS 1309-37-1)

Acute

Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

May cause cancer by inhalation. This product has the potential for generation of respirable dust Carcinogenicity

during handling and use. Dust may contain respirable crystalline silica. Crystalline silica (inhaled in the form of cristobalite or quartz) has been classified by IARC, NTP and ACGIH as a known human carcinogen and suspected human carcinogen respectively. Overexposure to dust may result in pneumocononiosis, a respiratory disease caused by inhalation of mineral dust, which can lead to fibrotic changes to the lung tissue, or silicosis, a respiratory disease caused by inhalation of silica dust, which can lead to inflammation and fibrosis of the lung tissue. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

May cause delayed lung injury.

Security Polymer Grout SDS US

IARC Monographs. Overall Evaluation of Carcinogenicity

Iron oxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - May cause respiratory irritation.

single exposure

Specific target organ toxicity -

repeated exposure.
Aspiration hazard

May cause damage to organs (Lung) through prolonged or repeated exposure.

Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

1. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. No data is available on the degradability of this product.

Persistence and degradability Bio-accumulative potential

Mobility in soil
Other adverse effects

No data available.
No data available.
None known.

2. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packagingSince emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

3. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

1. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard,

29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Security Polymer Grout SDS US

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

> Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes.

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Iron oxide (CAS 1309-37-1) Limestone (CAS 1317-65-3) Portland Cement (CAS 65997-15-1) Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Iron oxide (CAS 1309-37-1) Limestone (CAS 1317-65-3) Portland Cement (CAS 65997-15-1) Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Iron oxide (CAS 1309-37-1) Limestone (CAS 1317-65-3) Portland Cement (CAS 65997-15-1) Quartz (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)) Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Issue date: 23-May-2016

Security Polymer Grout

Version #: 01

Revision date: -

933653

7/8

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 23-May-2016

Revision date Version # 01

HMIS® ratings Health: 3*

Flammability: 0 Physical Hazard: 0

NFPA ratings



Disclaimer

Southern Grouts and Mortars cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Security Polymer Grout SDS US